



General use



Stay rope



Agriculture and livestock



## Steel Wire Rope ROPETEX S42

### Product information

**ROPETEX**

SZ

G



ROPETEX S42 is a wire rope for general purposes like hanging signs, small stays and in agriculture, but not for lifting. It's most used in small diameters up to 6 mm. ROPETEX S42 is equipped with a Fibre Core (FC).

ROPETEX S49 is the same rope but has a Wire Strand Core (WSC).

**Rope construction:** 6x7-FC

**Marking:** According to standard

**Temperature range:** -40°C up to +100°C

**Standard:** EN 12385-4

**Warning:** Not to be used for lifting purposes

**Fill factor:** 0,47

Part Code	Rope Diameter,	Tensile strength N/mm <sup>2</sup>	Steel area mm <sup>2</sup>	Min. Breaking force kN	Finish	Rope lay.	Weight kg/100m
101100204270030	2	1,960	1.48	2.6	Galvanized	sZ	1.38
101100304270030	3	1,960	3.32	5.86	Galvanized	sZ	3.11
101100404270030	4	1,960	5.9	10.4	Galvanized	sZ	5.52
101100504270030	5	1,960	9.23	16.3	Galvanized	sZ	8.63
101100604270030	6	1,960	13.3	23.4	Galvanized	sZ	12.4