



Stay rope



Agriculture and livestock



## Steel Wire Rope ROPETEX S19 Stainless Steel

### Product information

**ROPETEX**

S

Z

SS\*



ROPETEX S19 is a stainless steel wire rope. It's very corrosion resistant and durable, well suited for marine applications. The S19 rope has very little stretch which makes it excellent for standing rigging, stays, controls and architectural balustrades and green walls.

ROPETEX S19 can be provided with swaged terminals as end fittings.

**Rope construction:** 1x19

**Material:** AISI 316 / EN 1.4401

**Marking:** According to standard

**Temperature range:** -40°C up to +200°C

**Standard:** EN 12385-10

*except material*

**Warning:** Not to be used for lifting purposes

**Fill factor:** 0,74

Part Code	Rope Diameter,	Steel area mm <sup>2</sup>	Min. Breaking force kN. 1570 N/mm <sup>2</sup>	Finish	Weight kg/100m
108100101620018	1	0.58	0.83	Stainless	0.49
108100151620018	1.5	1.31	1.86	Stainless	1.09
108100131620018	1.25	0.91	1.29	Stainless	0.74
108100201620018	2	2.33	3.3	Stainless	1.94
108100251620018	2.5	3.65	5.16	Stainless	3.03
108100301620018	3	5.25	7.43	Stainless	4.37
108100401620018	4	9.34	13.2	Stainless	7.76
108100501620018	5	14.6	20.6	Stainless	12.1
108100601620018	6	21	29.7	Stainless	17.5
108100701620018	7	28.6	40.5	Stainless	23.8
108100801620018	8	37.4	52.8	Stainless	31
108101001620018	10	58.4	82.6	Stainless	48.5